

Chip PC 2006 Prodcuts Line EX-NG / EFI

Class	Model Name	CPU	Equiv. x86	Flash	RAM	Separate Video Memory	Video Output	Multi Screen Support	Legacy Port - Serial	Legacy Port Parallel	USB Ports	Audio Support	Max Resolution (Single Screen Configuration)	External Auxiliary Power	Power Over Ethernet	Management Software
USB-Only	EX-NG 6000	Alchemy Au 1550, 333 MHz RISC	800 MHz	32MB DOC P3	64 MB DDR	4 MB	Analog	N	N	N	3	N	1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
USB&Serial/Parallel Ports	EX-NG 6050	Alchemy Au 1550, 333 MHz RISC	800 MHz	32MB DOC P3	64 MB DDR	4 MB	Analog	N	1	1	3	Y	1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
Integrated PC/SC PKI Smart Card	EX-NG 6052	Alchemy Au 1550, 333 MHz RISC	800 MHz	32MB DOC P3	64 MB DDR	4 MB	Analog	N	1	1	3	Y	1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
USB-Only	EX-NG 6400	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	8 MB	Analog	N	N	N	3	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
USB&Serial/Parallel Ports	EX-NG 6450	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	8 MB	Analog	N	1	1	3	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
Integrated PC/SC PKI Smart Card	EX-NG 6452	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	8 MB	Analog	N	1	1	3	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
DVI Video, Dual Screen support	EX-NG 6500	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	8 MB	DVI-I/Analog	Dual Screen up to 1024x768 pixels @ 64 K (16 bit) colors	1	N	3	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
DVI Video, Dual Screen support, Integrated PC/SC PKI Smart Card	EX-NG 6552	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	8 MB	DVI-I/Analog	Dual Screen up to 1024x768 pixels @ 64 K (16 bit) colors	1	N	3	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
2xDVI Video, Dual/Quad Screen support	EX-NG 6600	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	16 MB	2 x (DVI-I/ Analog)	Quad (4) Screen up to 1024x768 pixels @ 64 K (16 bit) colors Dual Screen 1280x1024 pixels @ 16M (24bit) colors	N	N	4	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
Fiber Optic Network Interface	EX-NG 6460	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	8 MB	Analog	N	1	1	3	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global
Fiber Optic Network Interface	EX-NG 6462	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	8 MB	Analog	N	1	1	3	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur Global

LAN-Integrated, PoE	EFI-6700	Alchemy Au 1550, 333 MHz RISC	800 MHz	32MB DOC P3	64 MB DDR	4 MB	Analog	N	N	N	4	Y	1280x1024 pixels, 16 M (24 bit) colors	Y	Y	Xcalibur Global
LAN-Integrated, PoE	EFI-6800	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	8 MB	Analog	N	N	N	4	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	Y	Xcalibur Global
LAN-Integrated, PoE (DVI/Dual Screen support)	EFI-6900	Alchemy Au 1550, 500 MHz RISC	1.2 GHz	64MB DOC G3	128 MB DDR	8 MB	DVI-I/Analog	Dual Screen up to 1024x768 pixels @ 64 K (16 bit) colors	N	N	4	Y	1600x1200 @ 64 K (16bit) OR 1280x1024 pixels, 16 M (24 bit) colors	Y	Y	Xcalibur Global

Existing Xtreme PC - EX Models

USB-Only	EX-5000	Alchemy 333 MHz RISC	500 MHz	16 MB	32 MB	2 MB	Analog	N	N	N	2	N	1280x1024 pixels, 256 (8 bit) colors	Y	N	Xcalibur XP or Xcalibur Global
USB&Serial/Parallel Ports	EX-5070	Alchemy 333 MHz RISC	500 MHz	16 MB	64 MB	4 MB	Analog	N	Y	Y	3	Y	1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur XP or Xcalibur Global
Integrated PC/SC PKI Smart Card	EX-5072	Alchemy 333 MHz RISC	500 MHz	16 MB	64 MB	4 MB	Analog	N	Y	Y	3	Y	1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur XP or Xcalibur Global
USB&Serial/Parallel Ports	EX-5450	Alchemy 400 MHz RISC	800 MHz	32 MB	64 MB	4 MB	Analog	N	Y	Y	3	Y	1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur XP or Xcalibur Global
Integrated PC/SC PKI Smart Card	EX-5452	Alchemy 400 MHz RISC	800 MHz	32 MB	64 MB	4 MB	Analog	N	Y	Y	3	Y	1280x1024 pixels, 16 M (24 bit) colors	Y	N	Xcalibur XP or Xcalibur Global

Note: EX support of Xcalibur Global or Xcalibur XP 3.x is pending on EX Image version. Image 6.0 supports Xcalibur XP, Image 6.5.x supports Xcalibur Global